

Goodsense 2Ton 2.5Ton 3Ton Epa Euro 5 Lpg Forklift Machine Price Small Forklift Truck With Japanese Engine

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: Goodsense
- Model Number: FG15
- Minimum Order Quantity: Negotiable
- Price: Negotiable
- Packaging Details: Bare packaging
- Delivery Time: 30-40work days
- Payment Terms: T/T



Product Specification

- Model Number: FG15 FG20 FG25 FG30 FG35
- Rated Loading Capacity: 1.5 Ton 2 Ton 2.5 TON 3 Ton 3.5 TON
- Core Components: Motor, Pump, Gearbox, Engine
- Weight (KG): 6400 Kg
- Fork Length: 1070mm
- Fork Width: 150mm
- Overall Dimensions: 3260*1460*2270mm
- Service Weight: 6400kg
- Place Of Origin: China
- Brand Name: Goodsense
- Name: Forklift
- Condition: New
- Energy Supply: Reference Introduction
- Advantage: Small Vibration And Noise
- Highlight: goodsense diesel forklift truck,



More Images



for more products please visit us on rdforklift.com

Model		FG15	FG20	FG25	FG30
Rated load	kg	1500	2000	2500	3000
Load center distance	mm	500	500	500	500
Lift Height	mm	3000	3000	3000	3000
Free lift height	mm	155	240	240	165
Fork size(L×W×T)	mm	920×100×40	1070×122×40	1070×122×40	1070×125×45
Mast tilt angle(FR/RR)		6/12	6/12	6/12	6/12
Min. turning radius	mm	1955	2170	2230	2550
Min. right angle stacking length	mm	3365	3635	3695	4025
Min. right angle aisle width	mm	2155	2370	2430	2750
Min. ground clearance	mm	110	110	110	130
Height of overhead guard	mm	2060	2070	2070	2090
Maximum travel speed(Full load)	km/h	14.6	18	18	19
Maximum lift speed(Full load)	mm/s	510	500	500	560
Maximum drawbar pull(Full load)	KN	14	11.7	11.4	20
Gradeability		20	20	18	15
Overall length(Without forks)	mm	2235	2505	2580	2765
Overall width	mm	1080	1160	1160	1230
Fork height at maximum lift	mm	3930	3944	3944	4230
Mast height	mm	2010	1995	1995	2075
Tires	Front wheel	6.50-10-10PR	7.00-12-12PR	7.00-12-12PR	28×9-15-14PR
	Rear wheel	5.00-8-10PR	6.00-9-10PR	6.00-9-10PR	6.50-10-10PR
Wheelbase	mm	1400	1600	1600	1760
Self weigh	Kg	2790	3300	3660	4140

Battery	Voltage/capacity	V/Ah	12/80	12/80	12/80	12/80
Engine	Rated output	kw/r.p.m	31.2/2250	37.4/2300	37.4/2300	37.4/2300
	Rated torque	Nm/t.p.m	143.7/1600	176.5/1600	176.5/1600	176.5/1600
	Bore x stroke	mm	83×100	89×100	89×100	89×100
	Number of cylinders		4	4	4	4
	Displacement	L	2.164	2.488	2.488	2.488
Fuel tank capacity		L	49	55	55	55
Transmissions(FWD/RWD)			1/1 Manual shift	1/1 Manual shift	1/1 Manual shift	1/1 Manual shift
Operating pressure		Mpa	15.5	18.5	18.5	18.5
Tire type(FRV/RR)			Pneumatic	Pneumatic	Pneumatic	Pneumatic



Taizhou Ruidong Import and Export Co., Ltd



18367688514



gjq_0208@163.com



rdforklift.com

Room 606, East Building 3, Tengda Center, Jiaojiang District, Taizhou, Zhejiang, China